

## Overview

The LK Series metering pump is the largest in the high performance line of pumps from Walchem Corporation. The LK is a motor-driven, mechanically actuated diaphragm metering pump with a maximum capacity of 114 GPH (432 l/h) and a maximum pressure of 225 PSI (1.5 MPa).

The heart of the LK is a compact and very reliable dual-cam system drive and worm gear reducer. Roller bearings and oil bath lubrication ensure outstanding durability and wear resistance in continuous operation.

The LK Series is ideal for chemical feed applications in a wide range of fields, including water treatment, chemical process, agriculture, mining and paper.



## Summary of Key Benefits



### Liquid Ends

Drive from the gear reduction unit is directly transferred to the diaphragm. This design is economical, yet retains a high degree of versatility. Liquid ends are available in PVC, PVDF and 316 SS for handling acids, bases, solvents, polymers and slurries.



### Stroke Adjustment

Accurate and reliable stroke setting is accomplished with a micrometer dial of the springback stroke adjustment mechanism. This lockable mechanism is adjustable from 10 to 100%.



### Drive

The LK utilizes a dual-cam system drive with a built-in worm gear type speed reducer. The aluminum bronze worm gear and the tapered roller bearing provide efficient transmission of motor power to the pump. This compact and rigid mechanism provides maximum wear resistance in continuous operation over long periods of time.



### Motors

All of the standard models employ totally enclosed fan-cooled motors which are vertically mounted to save space. A variety of motor options are available, including explosion-proof and DC variable speed motors for external control by a 4-20 mA input signal.

## Ordering Information

LKN	45	A	—	VC
Pump Series	Capacity/Pressure	Motor		Liquid End Materials

### PUMP SERIES

LKN = LKN Series motor-driven metering pump with NEMA 42C motor mounting flange

### CAPACITY/PRESSURE RATING

See chart on this page

### MOTOR CODE

- A = 115/230V, 60 Hz, 1 phase, 1/3 HP, 1725RPM, TEFC Frame 42C
- B = 230/460V, 60Hz, 3 phase, 1/3 HP, 1725 RPM, TEFC Frame 42C
- C = 190/380/230/460V, 50/60Hz, 3 phase, 1/3 HP, 1450/1725 TEFC Frame 42C
- D = 90VDC, 1 phase, 1/3 HP, 1750 RPM, TENV Frame 42C Variable Speed Motor, 115V Control
- E = 180VDC, 1 ph, 1/3 HP, 1750 RPM, TENV Frame 42C Variable Speed Motor, 230V Control
- F = 230/460V, 60Hz, 3 ph, 1/3 HP, 1725 RPM, Explosion Proof Motor, Class 1, Div.1, Group C & D
- N = No motor option / used with special motor requirements

### LIQUID END MATERIALS

See chart on this page

#### Notes:

- Walchem recommends the installation of a pressure relief valve and a pulsation dampener in the discharge line of the LK Series pumps. Contact your Walchem distributor for these and other control and accessory products from Walchem.
- Maximum viscosity at rated output is 1000 cps for VS and S6, 500 cps for VH and 300 cps for VC and TC.

## Capacity and Pressure Rating

Model	Capacity*		Max. Pressure PSI		Stroke Speed IPM		Connections	Net Weight lbs	
	LPH@ 50 Hz	GPH @ 60 Hz	PVC/PVDF	SS	50 Hz	60 Hz	NPT	PVC/PVDF	SS
LKN32	30	9.5	150	225	96	116	1/2"	26	37
LKN45	50	15.9	150	225	48	58	1/2"	31	46
LKN47	100	31.8	120	120	96	116	1/2"***	31	46
LKN55	158	53.4	75	75	48	58	1"	35	57
LKN57	360	114.3	45	45	96	116	1"	35	57

\* Capacities listed are at max. pressure

\*\* LKN47 with VS liquid end has 1" NPT connections

## Liquid End Materials

Type	VC	VH	VS	TC	S6
Application	Acid	Alkaline	Viscosity & slurries	Strong Acids	Solvents
Pump head	PVC	PVC	PVC	PVDF	SS316
Valve ball	CE	HC	HD/SS304	Alumina Ceramic	HC
Valve seat					
Type 32	FKM	EPDM	SS304	FKM	SS316
Type 45 to 57	PVC	PVC	SS304	PVDG	SS316
O-ring	FKM	EPDM	EPDM	FKM	-----
Valve gasket	PTFE	PTFE	PTFE	PTFE	PTFE
Diaphragm	PTFE + EPDM				

CE	Alumina Ceramic
FKM	Fluoroelastomer
HC	Hastelloy C276
PVDF	Polyvinylidene fluoride
EPDM	Ethylene propylene diene monomer

## ABOUT US

Walchem integrates its advanced sensing, instrumentation, fluid pumping and communications technologies to deliver reliable and innovative solutions to the global water treatment market.

Our in-house engineering is driven by quality, technology and innovation. For more information on the entire Walchem product line, visit: [www.walchem.com](http://www.walchem.com)



**WALCHEM**  
An Iwaki America Company

Walchem, An Iwaki America Incorporated Company  
Five Boynton Road Hopping Brook Park  
Holliston, MA 01746 USA  
Phone: 508-429-1110  
Fax: 508-429-7433  
[www.walchem.com](http://www.walchem.com)

180186.F Jan 2009