

APPLICATIONS:

















# WHEN TO USE A PULSATION DAMPENER

 Reduce pump pulsation, pipe vibration, and shaking up to 99%

hydrochlorite.

Protect plastic piping, joints, and fittings from breaking or leaking

Available in PVC and CPVC from 1/2" to 2" connections for hard to seal chemicals like sodium


- · Extend pump life and performance
- Minimize pump cavitation
- Limit damaging pressure surges caused by pump start-up and shut-down
- Remove tube motion that abrades and shortens tube life
- Eradicate splashing, foaming, or product degradation
- · Ensure accurate reading of flow meters and gauges
- Produce a smooth, even flow for spraying or filling







### PRINCIPLES OF OPERATION:




SENTRY operates on the principle that volume is inversely proportional to pressure. Compressed air or gas is introduced into the air chamber of the SENTRY Pulsation Dampener to a

specified pressure. The gas is entrapped by the elastomeric bladder, which prevents contact between the process fluid and compressed gas. (Without the bladder, the gas would dissolve into the fluid and cause product contamination). During pump discharge, fluid enters the wetted chamber of the SENTRY Pulsation Dampener, displacing the bladder, compressing the gas and absorbing the shock. During pump shift, liquid pressure decreases, the dampener gas expands, pushing fluid back into the process line, eliminating up to 99% of system shock and pulsation.


#### AVAILABLE MODELS:


HOUSING	BLADDER	CU. INCH	INLET SIZE	FASTENING
PVC	Hypalon	4	1/2"	Bolted
CPVC	PTFE	10	3/4"	Ring Band Plastic
	Viton	36	1"	Ring Band Metal
	Hall	85	2"	Threaded
		175		
		370	Bull Isl	PER LIE

## TYPICAL PULSATION DAMPENER DIMENSIONS:










# BLACOH FAMILY OF PRODUCTS:













601 Columbia Ave, Suite D, Riverside, CA 92507 • USA

Tel: (800) 603-7867 or (951) 342-3100 • Fax: (951) 342-3101

E-mail: sales@blacoh.com • Website: www.blacoh.com